CS299MXL2

PNEUMATIC UNDERPINNER

The new CS299MXL2 is designed to meet the needs of every framer looking for high quality joins and comfort of use, thanks to the adjustable fences and the new patented retractable Ultra clamps.

FEATURES OF THE CS299MXL2

• Wide joining capacity: 190mm stroke (7"½) For mouldings up to 150mm wide (6") and 112mm high (4" 2/5)

• Ultra Powerful Double-action « push and tighten » rebate clamp

Position one of the moulding pieces up to the guide, then lay the second piece roughly place. The special action of the clamps draws them accurately and firmly together. Indeed, the clamps literally bite into the rebate of the 2 pieces of mouldings to pull and tighten them very strongly against each other. This ensures a high quality join every time, even on very wide mouldings. **This is unique to Cassese.**

New retractable Ultra clamp system

Patented "Ultra" clamp system now retracts into table leaving a flat surface. Great for handling big frames!

Patented adjustable fences

Adjusts for « less than perfect » 45 cuts and backs not 90 to bottom, in order to prevent gaps in the top or bottom of the join.

- Clamping of mouldings activated by foot-pedal
- Wedge firing activated by push button

Automatic position lock

Carriage is locked in position during insertion of nails allowing for consistent stacking of nails.

- · Built-in extension arms for large frames
- New magnetic XL adjustable top clamp

Quickly adjust hold down height. Just change rubber end for hardwood or softwood. Now with quick-change magnetic hold-downs.

- Patented self-adjusting back supports
- · No tools required to change wedges' sizes

Uses only genuine Cassese patented cartridge wedges. They are color coded with a full range of sizes available (3, 5, 7, 10, 12, & 15) most available in hardwood and softwood versions. Quality and performance!


- No need to adjust the pressure of the wedge shooting system When changing between softwood wedges and hardwood wedges
- Minimum service required
- Button to adjust the pressure of the horizontal clamps.

To be used when you replace regular clamps with optional soft rubber clamps or when you join very softwood moulding.













	Mouldings	
	Width	5mm-150mm
	Height	7mm-112mm
	Smallest Internal Frame size	85mm x 85mm
	Weight	60 Kg
	Length	490mm
	Width	450mm
	Height	1100mm
-	Air supply	Compressed air at 7 bars using 5 litres per cycle





Optional Accessories



